




CONTROL
BEGINS HERE

GENSALT OT

1 ALL-IN-ONE CONTROL

All pool water quality management functions are centralised in a single interface:

- Water disinfection by salt chlorination
- Automatic pH (with the complementary pH Link module)
- Pool device control: lighting, single speed pump...




2 PEACE OF MIND

GenSalt OT solution offers optimal water quality all the time. The chlorinator comes with a 2-year unconditional warranty*.



3 EASY TO INSTALL

The GenSalt OT platform can be installed **in just 10 minutes** in any environment, thanks to its **patented Quick Fix system**.



SPECIFICATIONS



No maintenance

Self-cleaning electrodes via reverse polarity.

STOP


Safe-system

Automatic stop if there is no flow in the cell.

UNCONDITIONAL
GUARANTEE
UNCONDITIONAL

Unconditional Guarantee

On the control box and the cell, whatever the causes of damage.



Shutter Mode

Automatic reduction of chlorine production when the pool's roller shutters are closed (adjustable to 0% or 30%).

FOR WHICH TYPE OF POOL?

1 ALL TYPES OF SWIMMING POOLS



2 VOLUME OF WATER TREATED IN A TEMPERATE CLIMATE, FILTRATION 8 HR/DAY)



ACCESSORIES INCLUDED IN THE PACK



Cell Installation Kit



Flow switch kit

TECHNICAL INFORMATION

MODELS	GenSalt OT 10	GenSalt OT 18	GenSalt OT 25
Volume of water treated in a temperate climate (filtration: 8 h/day)	40 m ³	70 m ³	110 m ³
Nominal chlorine production	10 g/h	18 g/h	25 g/h
Power	60 W	100 W	140 W
User interface	4-line, backlit LCD screen		
Operating mode(s)	Normal, Boost (100%), Low (cover mode 0 to 30%)		
Timer	Timer 24h / 2 timers for chlorination 2 timers for single speed pump		
Equipment control*	Filtration pump (single speed), booster pump, lighting (White or colored Zodiac®)...		
Polarity reversal	Yes : 3, 5 or 8 h (Factory setting= 5 h)		
Salt level (recommended - min.)	4 g/L - 3,0 g/L minimum		
Safety	Low salt' indicator light: Reduced production to protect the electrode 'No flow' indicator light: Production is interrupted as long as conditions are not ideal		
Cell position	Horizontal or vertical		
Plumbing compatibility	DN50 mm, DN63 mm, 1 1/2" (48 mm)		
Protection index	IP43		
Electric power supply	220-240 VAC / 50 Hz (mains power cable with moulded plug)		

ASSOCIATED PRODUCTS



pH Link module (pH regulation)

This module automatically measures and regulates the water's pH. If necessary, corrective product is injected.

Salt water chlorinators offer an automatic and efficient disinfection solution. They are easy to use, offer complete water treatment and reduce maintenance.

2 YEAR
UNCONDITIONAL
WARRANTY

RCS Lyon 395 068 679 - © Crédits photos : ZODIAC® - ZODIAC® is a registered trademark of Zodiac International, S.A.S.U., used under license